

WATER TREATMENT SPECIALISTS

EQUIPMENT • SERVICE • SALT • SUPPLIES 609-758-1110 OR 732-792-1400

WWW.AQUAMECH.NET

Aqua Flo Under Sink Filtration Systems

Choose A Filtration System To Meet Your Needs

The 475 Quick Change Filter Series offers 3, 2 & Single Stage options to provide solutions for a variety of water problems including sediment, rust, bad taste & odor



Choose From Five Models:


- 1. Three Stage Ultra Filtration
- 2. Dual Stage Sediment / Taste & Odor
- 3. Single Stage Sediment
- 4. Single Stage Coconut Carbon Block
- 5. Single Stage Granular Activated Carbon



"Change filters in seconds without turning off water! No tools required!"

Choose A Filtration System

- 3 Stage Ultra Filtration reduces lead, VOC (pesticides, herbicides, chemicals), THM, chlorine, taste, odor & sediment as small as 0.2 microns.
- Dual Stage Sediment / Taste & Odor removes sediment, bad tastes and odors. 5 Micron removal.
- Single Stage Sediment removes suspended sediment that makes water cloudy. 5 Micron removal.
- Single Stage Coconut Carbon Block removes bad tastes & odors while filtering out particles as small as 10 microns.
- Single Stage Granular Activated Carbon removes bad taste and odor. Perfect for chlorine reduction on clean municipal water supplies





Standard chrome faucet included, Designer faucets available.



11.8"w x 4.5"d x 14.3"h



6.3"w x 3.9"d x 13.4"h



2.8"w x 3.2"d x 12.4"h

475 QC Series Filter Systems

Description	Filter 1	Filter 2	Filter 3
TRIPLE STAGE ULTRA FILTER	SED	coc	UF
DOUBLE STAGE DUAL FILTER	SED		coc
SINGLE STAGE COCONUT CARBON FILTER	coc		
SINGLE STAGE SEDIMENT FILTER	SED		
SINGLE STAGE GAC FILTER	GAC		

475 QC Series Filters

Description	MICRON	FLOW RATE	(GALLONS)
SEDIMENT FILTER SED-10 BLUE (475 Q SERIES)	5	1 GPM	900
CARBON FILTER COC-10 PURPLE (475 Q SERIES)	10	1 GPM	1,500
CARBON FILTER GAC-10 YELLOW (475 Q SERIES)		0.7 GPM	1,500
ULTRA FILTER UF-10 BLACK (475 Q SERIES)	0.2	0.7 GPM	1,500

Feed Water Guidelines		
Iron (Fe)	<0.2ppm	
Manganese (Mn)	<0.05ppm	
Hydrogen Sulfide	0.0ppm	
Turbidity	<1.0NTU	
Feed Water Pressure	40-100psi	
Temperature	40-100°F	
pH Range	3.0-11.0	

Note: Pretreatment suggested if conditions excee parameters. Must be installed on potable water.







WATER TREATMENT SPECIALISTS

EQUIPMENT • SERVICE • SALT • SUPPLIES 609-758-1110 OR 732-792-1400

WWW.AQUAMECH.NET